

127


NASA TECHNICAL MEMORANDUM

NASA TM X-64689

ACTUATOR PARTICIPATION IN A BENDING MODE IDENTIFICATION SYSTEM

By Zack Thompson and Perry Davis
Astrionics Laboratory

September 1972



NASA

*George C. Marshall Space Flight Center
Marshall Space Flight Center, Alabama*

(NASA-TM-X-64689) ACTUATOR PARTICIPATION
IN A BENDING MODE IDENTIFICATION SYSTEM Z.
Thompson, et al (NASA) Sep. 1972 19 p


N72-33380

CSCL 14B

Unclas

G3/14 43484

TECHNICAL REPORT STANDARD TITLE PAGE

| | | | |
|--|--|--|---------------------------------|
| 1. REPORT NO. TM X-64689 | 2. GOVERNMENT ACCESSION NO. | 3. RECIPIENT'S CATALOG NO. | |
| 4. TITLE AND SUBTITLE Actuator Participation in a Bending Mode Identification System | | 5. REPORT DATE September 1972 | 6. PERFORMING ORGANIZATION CODE |
| | | 8. PERFORMING ORGANIZATION REPORT # | |
| 7. AUTHOR(S) Zack Thompson and Perry Davis | | 10. WORK UNIT NO. | 11. CONTRACT OR GRANT NO. |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS George C. Marshall Space Flight Center Marshall Space Flight Center, Alabama 35812 | | 13. TYPE OF REPORT & PERIOD COVERED Technical Memorandum | |
| | | 14. SPONSORING AGENCY CODE | |
| 12. SPONSORING AGENCY NAME AND ADDRESS National Aeronautics and Space Administration Washington, D. C. 20546 | | | |
| 15. SUPPLEMENTARY NOTES Prepared by Astrionics Laboratory, Science and Engineering | | | |
| 16. ABSTRACT A hydraulic actuator designed for a thrust vector control system used as a shaker for a vehicle to determine the bending mode frequencies is described. The actuator is used as the prime mover and the frequency sensor for the flexible vehicle in a test tower. Advantages in using the actuator piston position with respect to a commanded position to obtain the bending mode frequencies are shown. | | | |
| 17. KEY WORDS resonant frequency dynamic filter bending mode identification traveling notch filter shake test | | 18. DISTRIBUTION STATEMENT Unclassified - unlimited  | |
| 19. SECURITY CLASSIF. (of this report) Unclassified | 20. SECURITY CLASSIF. (of this page) Unclassified | 21. NO. OF PAGES 18 | 22. PRICE \$ 3.00 |

BIBLIOGRAPHY

Davis, P. W.: Equations Describing the Engine Position Control System for the Saturn S-I Stage of the SA-5 Vehicle. M-ASTR-IN-63-7, Marshall Space Flight Center, Alabama, March 19, 1963.

Hosenthien, Hans H. and Borelli, M, T.: An Adaptive Tracking-Notch Filter for Suppression of Structural Bending Signals of Large Space Vehicles. NASA TMX-53000, October 1, 1963.

Kalange, M. A. and Neiland, V. R.: Saturn Engine Gimbal and Thrust Vector Control System. SAE National Conference on Industrial Hydraulics, October 17-18, 1963.

Thompson, Zack and Alcott, R. J.: Apollo Booster Flight Control System Integration. Presented at the SAE-A-18 Committee Meeting, Houston, Texas, December 11-13, 1963.

Weaver, C. H.: Study of Engine Position Control Systems. M-ASTR-62-2, Marshall Space Flight Center, Alabama, January 19, 1962.


66


ACTUATOR PARTICIPATION IN A BENDING MODE IDENTIFICATION SYSTEM


By Zack Thompson and Perry Davis

The information in this report has been reviewed for security classification. Review of any information concerning Department of Defense or Atomic Energy Commission programs has been made by the MSFC Security Classification Officer. This report, in its entirety, has been determined to be unclassified.

This document has also been reviewed and approved for technical accuracy.


MELVIN BROOKS
Chief, Guidance and Control Systems Division


J. L. MACK
Chief, Systems Division


F. B. MOORE
Director, Astrionics Laboratory

ccc

TABLE OF CONTENTS

| | Page |
|---------------------------------------|------|
| INTRODUCTION | 1 |
| BENDING MODE IDENTIFICATION | 4 |
| BIBLIOGRAPHY | 11 |

LIST OF FIGURES

| Figure | Title | Page |
|--------|---|------|
| 1. | Vehicle and actuator test schematic | 5 |
| 2. | Actuator and load block diagram | 5 |
| 3. | Amplitude curves for transfer functions | 6 |
| 4. | Change in amplitude curves for load changes | 7 |
| 5. | Overall amplitude curves for load changes | 8 |
| 6. | Lumped parameter model | 9 |
| 7. | Actuator and load dynamics | 9 |
| 8. | Piston position with respect to piston command with multiple resonant load | 10 |

DEFINITION OF SYMBOLS

| <u>Symbol</u> | <u>Definition</u> | <u>Units</u> |
|------------------|--|-----------------------|
| $K_a G_1$ | amplifier transfer function | mA/deg |
| $K_v G_2$ | servovalve and actuator transfer function | deg/mA |
| G_3 | notch and shaping network | deg/deg |
| G_4 | load transfer function | deg/deg |
| F_o | open loop transfer function | deg/deg |
| ΔI | differential valve current | mA |
| ϵ | error signal | deg |
| β, β_p | piston ideal position and piston position unloaded, respectively | deg |
| β_p | actuator piston position | deg |
| β_e | engine position | deg |
| β_c | input command | deg |
| β_f | feedback signal | deg |
| S | Laplace operator | 1/S |
| f | frequency | Hz |
| K_p | pressure feedback gain | (M ⁵ /S)/N |
| H_1 | feedback gain | |

DEFINITION OF SYMBOLS (Concluded)

| <u>Symbol</u> | <u>Definition</u> | <u>Units</u> |
|---------------|-----------------------------|----------------|
| K_1 | $\frac{K_1 K_0}{K_1 + K_0}$ | N/M |
| A | piston area | M ² |

ACTUATOR PARTICIPATION IN A BENDING MODE IDENTIFICATION SYSTEM

INTRODUCTION

To design filters for the body bending frequencies of a flexible body vehicle, it is first necessary to determine the bending frequencies and their influence on vehicle stability. An analytical derivation is made to get the first approximation of the frequencies, then elaborate testing is conducted to verify the derived information. The vehicle or stage is suspended in the test tower by long cables arranged to permit free vibration (Fig. 1). To obtain frequency response information, the vehicle is then vibrated by connecting a large shaker to the aft part of the vehicle and sensing the motion of the vehicle at various points.

A thrust vector control system is capable of generating the forces necessary for shaking the vehicle. The bending mode frequencies can be determined from the actuator piston position.

To control the angular position of the engine, a servosystem that will attenuate the commands to the dynamic load in the vicinity of the load resonant frequency must be used. The desired servo would filter out the load resonant frequency and give the proper attenuation in the neighborhood of that frequency. A block diagram of a system of this nature is shown in Figure 2.

The transfer functions are as follows:

$$K_a G_1 = \frac{909}{\left[\frac{s^2}{(300)^2} + \frac{2(0.7)s}{300} + 1 \right]}$$

$$K_v G_2 = \frac{2.49}{s \left(\frac{s}{377} + 1 \right)}$$

$$G_3 = \frac{\left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}{\left[\frac{S^2}{(70.37)^2} + \frac{2(0.416)S}{(70.57)} + 1 \right]}$$

$$G_4 = \frac{1}{\left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}$$

An amplitude ratio frequency response of the system with the notch filter is shown in Figure 3. This system contains the dynamics of the load, the driving amplifier, the actuator, the servovalve, and the necessary dynamics to give the proper response.

In a multiengine control system, it is desirable from a hardware viewpoint to design one servoloop that can be interchangeable from engine to engine. Because of the tolerance used in manufacturing the stage structure, the engine, and the actuators, it is difficult to predict exactly what the resonant frequency of the load will be. It is desirable to have a system that would track the resonant frequency of the load and adjust the servosystem notch so that it would always be set at the proper frequency.

The closed-loop transfer function of the actuation system contains a numerator term that is exactly equal to the denominator in the transfer function of the load. The numerator term exists because the hydraulic fluid is compressible and the degree of compression is a function of the load acceleration, or force on the piston. The overall transfer function is a product of the servoloop and the load transfer functions. The development of this follows.

Since

$$\frac{\beta_p}{\beta_c} = \frac{F_o}{1 + F_o}$$

where

$$F_o = \frac{22.64 \left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}{S \left(\frac{S}{377} + 1 \right) \left[\frac{S^2}{(300)^2} + \frac{2(0.7)}{300} S + 1 \right] \left[\frac{S^2}{(70.57)^2} + \frac{2(0.416)}{70.57} S + 1 \right]}$$

$$G_4 = \frac{1}{\left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}$$

$$\frac{\beta_p}{\beta_c} = \frac{22.64 \left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}{S \left(\frac{S}{377} + 1 \right) \left[\frac{S^2}{(300)^2} + \frac{2(0.7)}{300} S + 1 \right] \left[\frac{S^2}{(70.57)^2} + \frac{2(0.416)}{70.57} S + 1 \right] + 22.64 \left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}$$

The parameters of the load can be changed at random to produce any natural frequency, and the notch filter will always be at the proper frequency.

$$\frac{\beta_e}{\beta_c} = \left(\frac{F_o}{1 + F_o} \right) (G_4)$$

$$\frac{\beta_e}{\beta_c} = \left\{ \frac{22.64 \left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)}{S \left(\frac{S}{377} + 1 \right) \left[\frac{S^2}{(300)^2} + \frac{2(0.7)}{300} S + 1 \right] \left[\frac{S^2}{(70.57)^2} + \frac{2(0.416)}{70.57} S + 1 \right] + 22.64 \left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)} \right\} \left[\frac{1}{\left(\frac{S^2}{\omega_n^2} + \frac{2\zeta}{\omega_n} S + 1 \right)} \right]$$

A representation of the traveling notch is shown in Figures 4 and 5. The natural frequency of the dynamic load was the only parameter varied.

To obtain tracking and the proper amount of attenuation for a dynamic load, it is necessary for the actuator piston position (β_p) to be a function of engine acceleration. This is how the transfer function β_p/β_i is obtained. The traveling notch and associated shaping networks are mechanical components and are installed within the actuator body.

BENDING MODE IDENTIFICATION

It has been established that the actuator will produce a notch at the resonant frequency of the load and that the notch will follow changes to the resonant frequency. To evaluate the actuation system to see if it would also produce a notch for loads that have more than one resonant frequency, the lumped parameter model in Figure 6 was used. The following equations must be solved simultaneously to obtain a load to the actuator.

$$F = K_0 (\beta - \beta_p)$$

$$0 = -K_0 \beta + (K_1 + K_0) \beta_p - K_1 \beta_1$$

$$0 = -K_1 \beta_p + (K_2 + K_1 + M_1 S^2) \beta_1 - K_2 \beta_2$$

$$0 = -K_2 \beta_1 + (K_2 + K_3 + M_2 S^2) \beta_2 - K_3 \beta_3$$

$$0 = -K_3 \beta_2 + (K_3 + M_3 S^2) \beta_3$$

A block diagram of these equations and the actuator dynamics is shown in Figure 7.

A frequency response of this system β_p / β_c is shown in Figure 8.

These frequencies and the lumped parameters were not intended to simulate any particular vehicle bending frequencies. This simulation does illustrate how an actuator can be used to shake a test vehicle and use the actuator piston position to determine the bending frequencies. The piston position potentiometer voltage can be of any magnitude necessary to achieve desired resolution and sensitivity.

The same conventional sensors presently used on this type of test may be used.




Figure 1. Vehicle and actuator test schematic.




Figure 2. Actuator and load block diagram.




Figure 3. Amplitude curves for transfer functions.




Figure 4. Change in amplitude curves for load changes.




Figure 5. Overall amplitude curves for load changes.




Figure 6. Lumped parameter model.




Figure 7. Actuator and load dynamics.




Figure 8. Piston position with respect to piston command with multiple resonant load.